Goral Vision

Step 1: Take out CarPlay host / Suction Cup stand / Glass plate

Please check if there are the above-mentioned items in the box



Step 2: Check the stand and the back of the host

check the mortise of the host and the tenon of the stand. Align the mortise, then assemble them and make a 'click' sound (please refer Step 3 to assemble it)





Step 3: How to easily assemble

Please refer to Figure 1 and Figure 2 to align and combine the stand and the host It makes the combination easily.

Note: there must be a 'click' sound to confirm the assembly completed.

The host may fall while using it if there is no 'click' sound.

Suction cop direction can be turned after assemble. And the direction depends on your install \triangle position (windshield or consle). Please use the glass plate if you install the hist no the console. (Its a bit tight during the first assembly. Remind you to assemble them with two hands.) (When you remove the stand. the gesture is the same as Fig.1, just upside down the host.)



The method of sound output

FM transmitte: This is a simple way to output audio from a car stereo. Due to the local FM radio channel allocation of various regions, suggest you use an empty channet to avoid noise and

Audio Aux out: To get the perfect CarPlay sound output from the car stereo, We suggest using

'Audio Aux out'.
Please check the connection below.





Connect the audio out of the host to the car stereo by audio cable







Step 4: Install the suction cup (two stage button)

When installing the suction cup stand, please note after the suction cup attached to the glass, be sure to press the button to the second stage. The host may fall and damage if the suction cup is not fully buckled.



Step 5: Installation position samples



 (\Box)



Note Please use TRS type audio cable (3 contacts).

